

FoxTerm Info: Logging started.  
XSnCMP > ?  
XSnCMP > variables:  
AAF=1  
ADR=0  
AM1=0  
AM2=0  
AM3=0  
AN1=1  
AN2=1  
AN3=1  
AT1=10  
AT2=10  
AT3=10  
AZA=0  
BVT=3680  
CAV=1  
CSD=1  
DC1='.' (0x2E)  
DC2='.' (0x2E)  
DC3='.' (0x2E)  
DHC=1  
DM1=';' (0x3B)  
DM2=';' (0x3B)  
DM3=';' (0x3B)  
DNA=uSonic-3\_Cage\_MP\_0111067260  
DNR=0111067260  
DNS=DHCP: 000.000.000.000, STAT: 192.168.178.254  
DOP=2018-08-08 09:11:23 : DO1=0x000001af  
DPN=5001  
DPW=\*\*\*\*\*  
DTI=2018-10-18 07:00:07  
EC1=1  
EC2=1  
EC3=1  
FR1=0  
FR2=0  
FR3=0  
FJA=0; 10; 0  
FJI=0; 10; 0  
FT0=000.000.000.000  
FT1=21  
FT2=  
FT3=\*\*\*\*\*  
FT4=  
FT5=  
FTC=1  
GWY=DHCP: 000.000.000.000, STAT: 192.168.178.247  
HDD=0  
HTM=0  
HTT=450  
HWR=10  
IPA=DHCP: 000.000.000.000, STAT: 192.168.178.123  
KEY=1  
LBT=2018-10-18 06:59:43  
LCT=2018-10-18 05:55:31  
MAC=0X70;B3;D5;A6;D0;2B  
MTD=5.0  
MRD=1.0  
NB1=3  
NB2=3  
NB3=3  
NLC=1  
NLD=1  
NM1=31  
NM2=31  
NM3=31  
NT0=178.063.009.212  
NT1=0.pool.ntp.org  
NTP=0  
OD1=0

18.10.18 Sc

OD2=0  
OD3=0  
OI1=0  
OI2=0  
OI3=0  
OPN=5000  
PCD=0  
PDN=0  
PN0=Default parameter set  
PN1=Default parameter set  
PN2=Default parameter set  
PN3=Default parameter set  
PNR=0x0021  
PR1=1  
PR2=1  
PR3=1  
SBR=57600  
SFR=10000  
SNR=0111067260  
SPW=\*\*\*\*\*  
SUB=DHCP: 000.000.000.000, STAT: 255.255.255.000  
SY1=0  
SY2=0  
SY3=0  
SO1=0  
SO2=0  
SO3=0  
TMD=0  
TYP=Metek USonic-3 Cage MP  
TZO=+00  
VNR=B.23RX  
VTS=2018-10-16 17:01:16  
EOT  
XSnCMP > RST  
XSnCMP > MCU Global Reset

---

Flash-Loader V1.34  
Date 2018-10-18 07:00:11

---

The Unique Device Info:  
Description : Cage Multipath RX63N  
Major-ID : 0x010B  
Device-ID : 0111067260  
MAC-Address : 70:B3:D5:A6:D0:2B

---

Current Firmware Info:  
Version : 010B\_023RX  
Baud Rate : 57600

---

XSnCMP > Multi Path Ultrasonic Anemometer C A G E

FoxTerm Info: Logging stopped.