

# Vector™ VR500 Smart Antenna

## OEM Hardware for Machine Control Systems



key features

- Simple all-in-one RTK capable heading solution
- Athena™ RTK and Atlas® L-band capable
- Integrated IMU delivers fast start-up times and provides heading during temporary GNSS loss
- Fully rugged IP69, MIL-STD810G, MIL-STD202F, IEC 60068-2 compliant solution for the harshest environments

---

The Vector VR500 is the first rugged all-in-one multi-frequency, multi-GNSS smart antenna which provides RTK-level position and precise heading. This rugged design is compliant to IP69, MIL-STD810G, MIL-STD-202F, and IEC 60068-2 standards for water ingress, shock, and vibration for the harshest environments. The VR500 is a great solution for machine control and other challenging applications.

The all-in-one VR500 with set antenna separation provides consistent and reliable position and heading accuracy.



Precision@HGNS.com  
www.HGNS.com

# Vector VR500 Smart Antenna

## GNSS Receiver Specifications

Receiver Type:	Vector GNSS RTK Receiver	
Signals Received:	GPS, GLONASS, BeiDou, Galileo, QZSS, IRNSS and Atlas	
Channels:	744	
GPS Sensitivity:	-142 dBm	
SBAS Tracking:	3-channel, parallel tracking	
Update Rate:	10 Hz standard, 50 Hz optional	
Timing (1PPS) Accuracy:	20 ns	
Rate of Turn:	100°/s maximum	
Cold Start:	40 s (no almanac or RTC)	
Warm Start:	20 s typical (almanac and RTC)	
Hot Start:	5 s typical (almanac, RTC and position)	
Heading Fix:	10 s typical (Hot Start)	
Antenna Input Impedance:	50 Ω	
Maximum Speed:	1,850 mph (999 kts)	
Maximum Altitude:	18,288 m (60,000 ft)	
Differential Options:	SBAS, Atlas (L-band), RTK	

## Accuracy

Positioning:	Horizontal (95%)	Vertical (95%)
Autonomous, no SA <sup>2</sup> :	1.2 m	2.5 m
SBAS (WAAS) <sup>2</sup> :	0.25 m	0.5 m
Atlas (L-band) <sup>2,8</sup> :	0.04 m	0.08 m
RTK <sup>1</sup> :	10 mm + 1 ppm	20 mm + 2 ppm
Heading (RMS):	< 0.2°	
Pitch/Roll (RMS):	1°	
Heave (RMS):	30 cm (DGPS) <sup>6</sup> , 10 cm (RTK) <sup>6</sup>	

## L-Band Receiver Specifications

Channels:	1530 to 1560 MHz
Sensitivity:	-130 dBm
Channel Spacing:	5 kHz
Satellite Selection:	Manual or Automatic
Reacquisition Time:	15 sec (typical)
Processor:	DSP for demodulation and protocol decoding module provides processing for the differential algorithms

## Communications

Ports:	1x full-duplex RS-232/RS-422, 1x RS232, 2x CAN, 1x Ethernet
Baud Rates:	4800 - 115200
Radio Interfaces:	Bluetooth 2.0 (Class 2), Wi-Fi 2.4 GHz, UHF (400 MHz)
Correction I/O Protocol:	Atlas, Hemisphere GNSS proprietary, RTCM v2.3 (DGPS), RTCM v3 (RTK), CMR, CMR+ <sup>1</sup>
Data I/O Protocol:	NMEA 0183, Hemisphere GNSS binary
Timing Output:	1PPS, CMOS, active low, falling edge sync, 10 kΩ, 10 pF load
Event Marker Input:	CMOS, active low, falling edge sync, 10 kΩ, 10 pF load
Heading Warning I/O:	Open relay system indicates invalid heading

## Power

Input Voltage:	9-32 VDC
Power Consumption:	10.5W Maximum (All signals and L-band)
Current Consumption:	1.2A Maximum
Power Isolation:	No
Reverse Polarity Protection:	Yes

## Environmental

Operating Temperature:	-40°C to +70°C (-40°F to +158°F)
Storage Temperature:	-40°C to +85°C (-40°F to +185°F)
Humidity:	95% non-condensing
Mechanical Shock:	50Gs, 11ms half sine pulse, 10 shocks in each direction and axis, total 60 shocks
Vibration:	Operational IEC 60068-2-29 MIL-STD-810G Vibration Sine: 30.6Grms MIL-STD-810G SAE J1211 ISO 16750-3:2007 Vibration Random: 5.96Grms IEC 60068-2-64 MIL-STD-202F
EMC:	EN 13309 Construction Machinery ISO 13766 Earth Moving E-Mark FCC part 15 Subpart B, CISPR22
IMO Wheelmark Certification:	No
Enclosure:	IP69

## Mechanical

Dimensions:	66.3L x 20.9 W x 14.6 H cm
Weight:	2.1kg
Status Indications (LED):	Power, GNSS Lock, Heading, UHF corrections
Power/Data Connector:	22-pin environmentally sealed

## Aiding Devices

Gyro:	Provides smooth heading, fast heading reacquisition and reliable < 0.5° per min heading for periods up to 3 min. when loss of GPS has occurred <sup>4</sup>
Tilt Sensors:	Provide pitch, roll data and assist in fast start-up and reacquisition of heading solution

<sup>1</sup> Depends on multipath environment, number of satellites in view, satellite geometry, no SA, and ionospheric activity

<sup>2</sup> Depends on multipath environment, number of satellites in view, WAAS coverage and satellite geometry

<sup>3</sup> Depends on multipath environment, number of satellites in view, satellite geometry, baseline length (for differential services), and ionospheric activity

<sup>4</sup> Based on a 40 second time constant

<sup>5</sup> Hemisphere GNSS proprietary

<sup>6</sup> Requires a Hemisphere GNSS subscription

## Authorized Distributor:



Copyright Hemisphere GNSS, Inc. All rights reserved. Specifications subject to change without notice.

Hemisphere GNSS, aRTK, Athena, Atlas, BaseLink, Crescent, Eclipse, SmartLink, SureFix, Tracer, and Vector are trademarks of Hemisphere GNSS, Inc.

Rev. 07/18



Hemisphere GNSS, Inc.  
8515 E. Anderson Drive  
Scottsdale, AZ, USA 85255

Toll-Free: +1 (855) 203-1770  
Phone: +1 (480) 348-6380  
Fax: +1 (480) 270-5070  
Precision@HGNS.com  
www.HGNS.com